

EMPLOYEE TRAINING RECORD

TRAINING TITLE **Aerators**

KEY TEACHING POINTS

Guardrails are installed on the tank side of usual work areas or walkways. Never go into unguarded areas alone.

When working on Y-walls, or other unguarded areas where work is done infrequently, at least two people should do the work. Approved life preservers with attached handlines are accessible at strategic locations around the aerator. You are to wear a safety harness with a life line when servicing aerator spray nozzles and other items around an aerator.

When removing or installing diffusers, be aware of the limitations of your working area. Inspect and properly position hoist and other equipment used in servicing swing diffusers.

When it is necessary to work in an empty aerator, test the atmosphere within the aerator prior to entry because a hazardous condition may exist if the unit has not been thoroughly cleaned. Lower yourself into the aerator carefully. Ladders are awkward and dangerous, but if properly positioned, so that they will not slip or twist they will provide access.

Aerators are confined spaces. Follow all confined space procedures.

TEST

QUESTION	ANSWERS	
	TRUE	FALSE
1. Guardrails are installed on the sides of tanks to protect you from falling in.	<input type="checkbox"/>	<input type="checkbox"/>
2. Test the atmosphere in an aerator to make sure no hazards exist.	<input type="checkbox"/>	<input type="checkbox"/>
3. Aerators are not confined spaces because they have open tops.	<input type="checkbox"/>	<input type="checkbox"/>
4. When working in an aerator, it is necessary to lockout/tagout/blockout all potential energy sources.	<input type="checkbox"/>	<input type="checkbox"/>
5. Only one person is necessary when working on Y-walls.	<input type="checkbox"/>	<input type="checkbox"/>
EMPLOYEE'S NAME	EMPLOYEE'S SIGNATURE	DATE
INSTRUCTOR'S NAME	INSTRUCTOR'S SIGNATURE	DATE

1. True 2. True 3. False 4. True 5. False