

EMPLOYEE TRAINING RECORD

TRAINING TITLE AIRLESS PAINT SPRAYER EQUIPMENT MISUSE HAZARD

KEY TEACHING POINTS

GENERAL SAFETY

- Misuse of the spray equipment or accessories, such as over pressurizing, modifying parts, using incompatible chemicals and fluids, or using worn or damaged parts, can cause them to rupture and result in fluid injection, splashing in the eyes or on the skin, or other serious injury, fire, explosion or property damage.
- Never alter or modify any part of this equipment; doing so could cause it to malfunction.
- Check all spray equipment before each use and repair or replace worn or damaged parts immediately.

PERSONAL PROTECTIVE EQUIPMENT

- Always wear protective eyewear, gloves, clothing and respirator as recommended by the fluid and solvent manufacturer. Wear ear - noise protection when working near the sprayer when the engine is running.

SYSTEM PRESSURE

- The spray can develop high working pressures (3000 psi). Be sure all spray equipment and accessories used are rated to withstand the working pressure of the equipment. Do not exceed the maximum working pressure of any component or accessory used in the system.

FLUID AND SOLVENT COMPATIBILITY

- All chemicals used in the sprayer must be chemically compatible for the wetted parts shown in the technical data of the operators manual.

TEST

QUESTION	ANSWERS	
	TRUE	FALSE
1 All chemicals used in the sprayer must be chemically compatible for the wetted parts.		
2 Misuse of the spray equipment or accessories, such as over pressurizing, modifying parts, using incompatible chemicals and fluids, or using worn or damaged parts, can cause them to rupture.		
3 Be sure all spray equipment and accessories used are rated to withstand the working pressure of the equipment.		
4 Always wear protective eyewear, gloves, clothing and respirator as recommended by the fluid and solvent manufacturer.		
5 Never alter or modify any part of spray equipment.		
EMPLOYEE'S NAME	EMPLOYEE'S SIGNATURE	DATE
INSTRUCTOR'S NAME	INSTRUCTOR'S SIGNATURE	DATE

1 T 2 T 3 T 4 T 5 T
