

EMPLOYEE TRAINING RECORD		
TRAINING TITLE	Fueling - Petroleum, Oil and Lubricants	
KEY TEACHING POINTS		
<ul style="list-style-type: none"> <li>• No internal combustion engine fuel or lubricant tank shall be filled with the engine running unless that type of engine is specifically designed to accommodate these actions (such as, the engines in the Power Generation Facility which have automatic oilers). Fueling shall be done in such a manner that the likelihood of spillage is minimal. If a spill occurs it shall be washed away completely, evaporated or absorbed by an absorbent designed for that purpose. Action shall be taken to control vapors before restarting the engine. Fuel tank caps shall be replaced before starting the engine.</li> <li>• Open lights, open flames, or sparking or arcing equipment, except that which is an integral part of an automotive equipment, shall not be used within fifty (50) feet of fuel storage tanks, pumps, drums, or internal combustion engine while being fueled with flammable liquids.</li> <li>• Refueling with portable containers shall be done with approved safety containers equipped with an automatic closing cap and flame arrester.</li> </ul>		
TEST		
QUESTION	ANSWERS	
	TRUE	FALSE
1. Do not fill engine fuel or lubricants with the engine running.	<input type="checkbox"/>	<input type="checkbox"/>
2. There can be no open lights, flames, or sparking or arching within 50 feet of a fueling site.	<input type="checkbox"/>	<input type="checkbox"/>
3. Any container can be used to fill an engine.	<input type="checkbox"/>	<input type="checkbox"/>
4. Replace fuel tank caps before starting an engine.	<input type="checkbox"/>	<input type="checkbox"/>
5. Do not worry about spilled gasoline.	<input type="checkbox"/>	<input type="checkbox"/>
EMPLOYEE'S NAME	EMPLOYEE'S SIGNATURE	DATE
INSTRUCTOR'S NAME	INSTRUCTOR'S SIGNATURE	DATE

1. True 2. True 3. False 4. True 5. False
---