

EMPLOYEE TRAINING RECORD		
TRAINING TITLE Fall Protection - Positioning Device Systems		
KEY TEACHING POINTS		
<ul style="list-style-type: none"> • Positioning devices shall be rigged such that an employee cannot free fall more than 2 feet. • Positioning device systems shall be inspected prior to each use for wear, damage, and other deterioration, and defective components shall be removed from service. • Harnesses and components shall be used only for employee protection and not to hoist materials. • The use of non-locking snaphooks is prohibited. • Anchorage points for positioning devices shall be capable of supporting two times the intended load or 3,000 pounds, whichever is greater. • Positioning devices are not a substitute for fall protection. Fall protection is required for work being done over 6 feet from the surface below. 		
TEST		
QUESTION	ANSWERS	
	TRUE	FALSE
1 Positioning devices are not a substitute for fall protection.	<input type="checkbox"/>	<input type="checkbox"/>
2 Fall protection is required for work being done over 6 feet from the surface below.	<input type="checkbox"/>	<input type="checkbox"/>
3 Positioning devices shall be rigged such that an employee cannot free fall more than 2 feet.	<input type="checkbox"/>	<input type="checkbox"/>
4 Positioning device systems shall be inspected prior to each use for wear, damage, and other deterioration, and defective components shall be removed from service.	<input type="checkbox"/>	<input type="checkbox"/>
5 The use of non-locking snaphooks is prohibited.	<input type="checkbox"/>	<input type="checkbox"/>
EMPLOYEE'S NAME	EMPLOYEE'S SIGNATURE	DATE
INSTRUCTOR'S NAME	INSTRUCTOR'S SIGNATURE	DATE

1. True 2. True 3. True 4. True 5. True
