

**EMPLOYEE TRAINING RECORD**

**TRAINING TITLE**      Sewer Rodder - Operation and Maintenance

**KEY TEACHING POINTS**

- Before driving vehicle, complete safety pre-operation checklist.
- Set up work location following established traffic control procedures.
- Check oil and hydraulic fluid in auxiliary engine.
- Grease fittings on reel before operating.
- Change oil in auxiliary engine every other week.
- Make sure the rods are tightened every other week.
- Make sure the dogs are not worn.
- Make sure the chain is tight at all times.
- Make sure that you have all the necessary screws needed to do the job.
- Make sure all gauges are working properly.
- Watch the reel speed and rod pressure at all times.
- Never stick your hands or arms inside rodding unit while engine is running.
- Do not bend the hose guide bar.
- Do not attempt to pull rods and rod guide out of sewer line with the truck.
- Make sure pressure is not too great going in and out of the line. Adjust pressure slowly.

**TEST**

QUESTION	ANSWERS	
	TRUE	FALSE
1. Never stick hands or arm inside rodder while running.		
2. Adjust pressure slowly when going in and out of line.		
3. Pull rods and rod guide out of line with the truck.		
4. Perform preventive maintenance inspection on equipment before use.		
5. The reel speed and rod pressure have nothing to do with safety.		
<b>EMPLOYEE'S NAME</b>	<b>EMPLOYEE'S SIGNATURE</b>	<b>DATE</b>
<b>INSTRUCTOR'S NAME</b>	<b>INSTRUCTOR'S SIGNATURE</b>	<b>DATE</b>

1. True 2. True 3. False 4. True 5. False